

Inductive sensor


NBN8-18GK50-Z1-1,1M-Y



- 8 mm non-flush
- Sturdy plastic housing



Dimensions



Technical Data

General specifications		
Switching function		Normally closed (NC)
Output type		Two-wire
Rated operating distance	s_n	8 mm
Installation		non-flush
Output polarity		DC
Assured operating distance	s_a	0 ... 6.48 mm
Reduction factor r_{Al}		0.46
Reduction factor r_{Cu}		0.41
Reduction factor r_{304}		0.78
Reduction factor r_{Brass}		0.52
Nominal ratings		
Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 300 Hz
Hysteresis	H	1 ... 10 typ. 2.5 %
Reverse polarity protection		yes
Short-circuit protection		pulsing

Release date: 2022-06-20 Date of issue: 2022-06-20 Filename: 70138017_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Voltage drop	U_d	3.2 ... 5.2 V typ. 4 V
Operating current	I_L	6 ... 100 mA
Off-state current	I_r	0.8 ... 1.2 mA typ. 1 mA
Switching state indicator		LED, yellow
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012
Approvals and certificates		
UL approval		cULus Listed, General Purpose, Class 2 Power Source E87056
CCC approval		CCC approval / marking not required for products rated ≤ 36 V
Ambient conditions		
Ambient temperature		-20 ... 70 °C (-4 ... 158 °F)
Mechanical specifications		
Connection type		cable
Housing material		PBT
Sensing face		PBT
Degree of protection		IP68 / IP69
Cable		
Number of cores		2
Core cross section		0.5 mm ²
Length	L	L = 1.1 m \pm max. 10 mm L1 = 100 mm \pm 5 mm L2 = 100 mm \pm 5 mm L3 = 150 mm \pm 5 mm L4 = 8 mm

Connection

