

Inductive sensor

NMB6-F104M-E2-FE-200MM-V3

- Sensing range 6 mm
- Ferrous targets
- Stainless steel sensing face
- 200 mm M8 male cordset with PUR jacket
- Power and output LEDs



Dimensions

Technical Data

General specifications			
Switching function			Normally open (NO)
Output type			PNP
Rated operating distance	s_n		6 mm
Installation			flush
Assured operating distance	s_a		0 ... 4.86 mm
Actuating element			Ferrous targets
Reduction factor r_{Al}			0
Reduction factor r_{Cu}			0
Reduction factor r_{304}			0.6 ... 0.8
Reduction factor r_{St37}			1
Output type			3-wire
Nominal ratings			
Operating voltage	U_B		10 ... 30 V DC
Switching frequency	f		20 Hz
Hysteresis	H		5 ... 15 typ. 10 %
Reverse polarity protection			reverse polarity protected
Short-circuit protection			yes
Voltage drop	U_d		≤ 2 V
Operating current	I_L		≤ 100 mA
Current consumption			≤ 22 mA
Off-state current	I_r		≤ 10 μ A
Indicators/operating means			
Operation indicator			Dual LED Green: power Yellow: output
Standard conformity			
Standards			EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates			
UL approval			cULus Listed, General Purpose
CCC approval			CCC approval / marking not required for products rated ≤ 36 V
Ambient conditions			
Ambient temperature			-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications			
Connection type			Cable connector M8 x 1 , 3-pin with PUR cable 200 mm

Release date: 2023-04-11 Date of issue: 2023-04-11 Filename: 915197_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Core cross section	0.34 mm ²
Housing material	Stainless steel 1.4305 / AISI 303
Degree of protection	IP67

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)

Accessories

	V3-WM-OR5M-POC	Female cordset single-ended M8 angled A-coded, 3-pin, POC cable welding-bead resistant orange, suitable for robotic applications, torsion resistant, oil resistant, molecularly cross-linked
	V3-GM-OR5M-POC	Female cordset single-ended M8 angled A-coded, 3-pin, POC cable welding-bead resistant orange, suitable for robotic applications, torsion resistant, oil resistant, molecularly cross-linked

Release date: 2023-04-11 Date of issue: 2023-04-11 Filename: 915197_eng.pdf